

Technical data

HC 180i P



Compactors Series HC
Compactor with padfoot drum

H256

HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

TECHNICAL DATA HC 180i P (H256)

Weights

Operating weight with cab	kg	17640
Operating weight with ROPS	kg	17305
Empty weight without cab, without ROPS	kg	16435
Max. operating weight	kg	18390
Axle load, front/rear	kg	11385/6255
Axle load for max. operating weight, front/rear	kg	11410/6980
Static linear load, front	kg/cm	53,20
French classification, value/class		75,37/VPM5
Wheel load per tyre, rear	kg	3127,5

Machine dimensions

Total length	mm	6527
Total height with cab	mm	3046
Total height with ROPS	mm	3054
Height loading, min.	mm	3046
Centre distance	mm	3267
Total width with cab	mm	2474
Maximum working width	mm	2140
Ground clearance, centre	mm	425
Kerb clearance, left/right	mm	462/462
Turning radius, inside	mm	4137
Slope angle, front/rear	°	31,6/25,7

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1697
Drum thickness, front	mm	30
Drum type, front		Padfoot
Height of the padfeet	mm	112
Padfeet, quantity		130

Tyre dimensions

Tyre size, rear		TR 23.1/18-26 12 PR
Width over tyres, rear	mm	2140
Number of tyres, rear		2

Diesel engine

Manufacturer		DEUTZ
Model		TCD 6.1 L6
Cylinders, quantity		6
Power ISO 14396, kW/PS/rpm		160,0/217,7/2000
Power SAE J1349, kW/HP/rpm		160,0/214,7/2000
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Travel drive

Speed, infinitely variable	km/h	0 - 11,9
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	55/61

Vibration

Vibration frequency, front, I/II	Hz	28/31
Amplitude, front, I/II	mm	2,15/1,35

Vibration

Centrifugal force, front, I/II	kN	330/260
--------------------------------	----	---------

Steering

Swing angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L	336
AdBlue/SCR reducing agent tank, capacity	L	32

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	104

EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Traction Control, manual | Steel scraper, for padfoot drum

OPTIONAL EQUIPMENT

Traction Control, automatic | ROPS cab with heating and air-conditioning system (FOPS, level I) | Seat belt monitoring device | Armrest comfort setting, left | Auxiliary heater | Tachograph | Fire extinguisher | Bluetooth interface for Smart Doc | Dozer blade | Frequency control | Automatic engine stop | Camera system | Back-up alarm | Working spotlights | Rotating beacon | Engine hood with electrical release mechanism | Coming Home function | Battery isolation switch | Additional mirror | Tool kit