

Technical data

# HC 160i C



**Compactors Series HC**  
Compactor with smooth drum

H254

## HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

**TECHNICAL DATA HC 160i C (H254)**

**Weights**

Operating weight with cab	kg	16390
Operating weight with ROPS	kg	16270
Empty weight without cab, without ROPS	kg	15415
Max. operating weight	kg	19140
Axle load, front/rear	kg	10845/5545
Axle load for max. operating weight, front/rear	kg	13170/5970
Static linear load, front	kg/cm	50,68
French classification, value/class		71,11/VM5
Wheel load per tyre, rear	kg	2772,5

**Machine dimensions**

Total length	mm	6315
Total height with cab	mm	3054
Total height with ROPS	mm	3054
Height loading, min.	mm	3054
Centre distance	mm	3266
Total width with cab	mm	2474
Maximum working width	mm	2140
Ground clearance, centre	mm	461
Kerb clearance, left/right	mm	477/477
Turning radius, inside	mm	4131
Slope angle, front/rear	°	34,2/23,7

**Drum dimensions**

Drum width, front	mm	2140
Drum diameter, front	mm	1504
Drum thickness, front	mm	45
Drum type, front		Smooth

**Tyre dimensions**

Tyre size, rear		AW 23.1-26 12 PR
Width over tyres, rear	mm	2122
Number of tyres, rear		2

**Diesel engine**

Manufacturer		JOHN DEERE
Model		JDPS 4045PSS
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		119,6/162,6/2000
Power SAE J1349, kW/HP/rpm		119,6/160,4/2000
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

**Travel drive**

Speed, infinitely variable	km/h	0 - 11,9
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	56/62

**Vibration**

Vibration frequency, front, I/II	Hz	28/31
Amplitude, front, I/II	mm	2,10/1,35
Centrifugal force, front, I/II	kN	330/260

**Steering**

Swing angle +/-	°	max. 12
Steering, type		Articulated steering

**Tank capacity/filling capacity**

Fuel tank, capacity	L	280
AdBlue/SCR reducing agent tank, capacity	L	32

**Sound level**

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	103

**EQUIPMENT**

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system

**OPTIONAL EQUIPMENT**

ROPS cab with heating and air-conditioning system (FOPS, level I) | Auxiliary heater | Tachograph | Bluetooth interface for Smart Doc | Automatic engine stop | Back-up alarm | JDLink | Working spotlights | Coming Home function | Battery isolation switch