

Technical data

HC 160i C P



Compactors Series HC
Compactor with padfoot drum

H254

HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

TECHNICAL DATA HC 160i C P (H254)

Weights

Operating weight with cab	kg	16280
Operating weight with ROPS	kg	16160
Empty weight without cab, without ROPS	kg	15305
Max. operating weight	kg	17620
Axle load, front/rear	kg	10735/5545
Axle load for max. operating weight, front/rear	kg	11650/5970
Static linear load, front	kg/cm	50,16
French classification, value/class		71,1/VP M5
Wheel load per tyre, rear	kg	2772,5

Machine dimensions

Total length	mm	6315
Total height with cab	mm	3054
Total height with ROPS	mm	3054
Total height with plastic protective roof	mm	3054
Height loading, min.	mm	3054
Centre distance	mm	3266
Total width with cab	mm	2474
Maximum working width	mm	2140
Ground clearance, centre	mm	461
Kerb clearance, left/right	mm	477/477
Turning radius, inside	mm	4131
Slope angle, front/rear	°	33,7/23,7

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1697
Drum thickness, front	mm	30
Drum type, front		Padfoot
Height of the padfeet	mm	112
Padfeet, quantity		130

Tyre dimensions

Tyre size, rear		TR 23.1/18-26 12 PR
Width over tyres, rear	mm	2154
Number of tyres, rear		2

Diesel engine

Manufacturer		JOHN DEERE
Model		JDPS 4045PSS
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		119,6/162,6/2000
Power SAE J1349, kW/HP/rpm		119,6/160,4/2000
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Travel drive

Speed, infinitely variable	km/h	0 - 11,9
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	59/66

Vibration

Amplitude, front, I/II	mm	2,15/1,35
Centrifugal force, front, I/II	kN	330/260

Steering

Swing angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L	280
AdBlue/SCR reducing agent tank, capacity	L	32

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	103

EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system

OPTIONAL EQUIPMENT

ROPS cab with heating and air-conditioning system (FOPS, level I) | Auxiliary heater | Tachograph | Bluetooth interface for Smart Doc | Automatic engine stop | Back-up alarm | JDLink | Working spotlights | Coming Home function | Battery isolation switch