

Technical data

# HD+ 120i VO



## Tandem rollers Series HD+

Tandem roller with vibration and oscillation drum

H304

### HIGHLIGHTS

- > Operating concept Easy Drive
- > 3-point articulation for even weight distribution and excellent directional stability
- > Innovative cabin concept for optimal visibility and high comfort
- > Compaction with oscillation
- > Digital ready

**TECHNICAL DATA HD+ 120i VO (H304)**

**Weights**

Operating weight with cab	kg lbs	12755 28,125
Operating weight with ROPS	kg lbs	12525 27,618
Empty weight without cab, without ROPS	kg lbs	11440 25,225
Max. operating weight	kg lbs	13780 30,385
Axle load, front/rear	kg lbs	6300/6455 13,891/14,233
Static linear load, front/rear	kg/cm lbs/in	31,82/32,60 178.2/182.6
French classification, value/class		30,47/VT2

**Machine dimensions**

Total length	mm in	5300 208.7
Total height with cab	mm in	2980 117.3
Total height with ROPS	mm in	3030 119.3
Height loading, min.	mm in	2140 84.3
Center distance	mm in	3900 153.5
Total width with cab	mm in	2145 84.4
Maximum working width	mm in	2150 84.6
Ground clearance, center	mm in	340 13.4
Curb clearance, left/right	mm in	900/900 35.4/35.4
Turning radius, inside	mm in	6280 247.2

**Drum dimensions**

Drum width, front/rear	mm in	1980/1980 78.0/78.0
Drum diameter, front/rear	mm in	1400/1400 55.1/55.1
Drum thickness, front/rear	mm in	19/19 0.7/0.7
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	170 6.7

**Diesel engine**

Manufacturer		DEUTZ
Model		TCD 4.1 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		115,0/156,4/2300
Power SAE J1349, kW/HP/rpm		115,0/154,1/2300
Exhaust emission standard		EU Stage V / EPA Tier 4

**Diesel engine**

Exhaust gas after-treatment		DOC-DPF-SCR
-----------------------------	--	-------------

**Travel drive**

Speed, infinitely variable	km/h mph	0-10,5 0.0-6.5
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	38/42

**Vibration**

Vibration frequency, front, level I/II	Hz vpm	40/50 2,400/3,000
Amplitude, front, level I/II	mm in	0,95/0,35 .037/.014
Centrifugal force, front, level I/II	kN lbs	160/95 36,000/21,375

**Oscillation**

Oscillation force, rear	kN lbs	170,48 38,358
Oscillation frequency, rear	Hz vpm	36 2,160
Tangential amplitude, rear	mm in	1,20 .047

**Steering**

Pendulum angle +/-	°	10
Steering, type		Articulated steering

**Water-sprinkling system**

Water sprinkling, type		Pressure
------------------------	--	----------

**Tank capacity/filling capacity**

Fuel tank, capacity	L Gal	260 68.7
AdBlue/SCR reducing agent tank, capacity	L Gal	20 5.3
Water tank, capacity	L Gal	1145 302.5

**Sound level**

Sound power level L(WA), guaranteed	db(A)	109
Sound power level L(WA), representative measurement	db(A)	107

**EQUIPMENT**

Scrapers foldable | Pressure water sprinkling system | ECO mode | Speed preselect | Track offset, hydraulic | Water filter system (3-fold) | Central water outlet

**OPTIONAL EQUIPMENT**